PAGE 03/15

Appln. No. 10/632,352

Attorney Docket No. DKT91043H

I. <u>Listing of Claims</u>

10/17/2007 PCHONP

00000038 231925

10632352

82-107. Cancelled.

91 :C:1202

50.00 DA

108. (Currently Amended) An adaptive drive system for a motor vehicle comprising, in combination,

a first drive line having a first drive shaft, a first differential, a first pair of axles, a first pair of wheels and at least one first speed sensor for providing a first drive line speed signal,

a second drive line having a second drive shaft, a second differential, a second pair of axies, a second pair of wheels and at least one second speed sensor for providing a second drive line speed signal,

a transfer case having an input, a first output adapted to drive said first drive line, a second output adapted to drive said second drive line and a clutch that is capable of being variably engaged and is operably disposed between said first output and said second output, wherein said clutch is capable of engagement levels between a predetermined minimum engagement and a predetermined maximum engagement, and

a microcontroller that receives said first driveline speed signal from said first speed sensor and said second driveline speed signal from said second speed sensor and determines [[a]] speed difference differences between said first and said second speed signals at a plurality of predetermined times, wherein said speed differences may vary at said plurality of times,

Attorney Docket No. DKT91043H

wherein at one of said plurality of predetermined times said clutch engagement increases if [[said]] a speed difference is greater than a first predetermined value and said clutch engagement is less than the predetermined maximum engagement level at said one of said plurality of predetermined times, wherein said predetermined value may vary at said plurality of predetermined times, and wherein at another of said plurality of predetermined times are said speed difference is less than a second another predetermined value and said clutch engagement is greater than said predetermined minimum engagement level at said another of said plurality of predetermined times.

- 109. (Currently Amended) The adaptive drive system of claim 108 wherein said first predetermined value <u>varies depending on then existing operating conditions of the vehicle at said plurality of predetermined times is greater than said second predetermined value.</u>
- 110. (Currently Amended) The adaptive drive system of claim [[108]] 109 wherein said operating conditions comprise one or more of vehicle speed, throttle position, steering angle, identity of an overrunning drive line, vehicle range and brake condition first predetermined value is less than said second predetermined value.
- 111. (Currently Amended) The adaptive drive system of claim 108 wherein said predetermined values are increased engagement of said clutch is in equal in magnitude amounts.



Attorney Docket No. DKT91043H

- 112. (Currently Amended) The adaptive drive system of claim [[108]] 111 wherein said predetermined times are decreased clutch engagement is in equal in duration amounts.
- 113. (Currently Amended): The adaptive drive system of claim 108 wherein said clutch engagement does not increase if said speed difference is less than said predetermined value decreased engagement of said clutch is by predetermined amounts when said speed signal difference is less than said second predetermined value at said predetermined times.
- 114. (Currently Amended): The adaptive drive system of claim 108 further including a throttle position sensor providing a signal to said microcontroller and wherein said [[first]] predetermined value reduces is reduced in magnitude as said signal from said throttle position sensor increases.
- 115. (Previously Presented): The adaptive drive system of claim 108 wherein said speed signals represent an average speed of an associated said pair of wheels.
- 116. (Currently Amended): The adaptive drive system of claim 108 wherein said clutch is engaged [[at]] to at least a minimum level of engagement at said <u>plurality</u> of predetermined times.

Attorney Docket No. DKT91043H

- 117. (Currently Amended): The adaptive drive system of claim 115 wherein said microcontroller reduces said predetermined values value as said predetermined minimum clutch engagement is increased.
- 118. (Previously Presented): The adaptive drive system of claim 108 wherein said clutch is a friction clutch pack having a plurality of interleaved discs.
- 119. (Currently Amended): The adaptive drive system of claim 108 further including a ball ramp actuator having an electromagnetic coil.
- 120. (Currently Amended): An adaptive drive system for a motor vehicle comprising, in combination,

a first drive line having a first differential, a first pair of axles, a first pair of wheels and at least one first drive line speed sensor,

a second drive line having a second differential, a second pair of axles and a second pair of wheels and at least one second drive line speed sensor,

a clutch operably disposed between said first drive line and said second drive line, and

a microcontroller that compares speed data from said first and said second drive line speed sensors during predetermined time intervals and wherein engagement of said clutch increases if a difference between speeds of said drivelines is greater than a [[first]] predetermined value during said predetermined time intervals, and engagement

Attorney Docket No. DKT91043H

of said clutch decreases if a difference between speeds of said drivolines is loss than a second predetermined value during said predetermined time intervals.

- 121. (Currently Amended): The adaptive drive system of claim 120 wherein said increased engagement of said clutch occurs in steps when said speed difference exceeds said [[first]] predetermined value during said predetermined time intervals.
- 122. (Currently Amended): The adaptive drive system of claim [[120]] 143 wherein said decreased engagement of said clutch occurs in steps when said speed difference does not exceed said second predetermined value during said predetermined time intervals.
- 123. (Previously Presented): The adaptive drive system of claim 121 or 122 wherein said steps are of equal magnitude.
- 124. (Previously Presented): The adaptive drive system of claim 121 or 122 wherein said steps are of equal duration.
- 125. (Currently Amended): The adaptive drive system of claim 120 wherein said clutch is engaged [[at]] to at least a minimum level of engagement during said predetermined times intervals.

Attorney Docket No. DKT91043H

126. (Currently Amended): The adaptive drive system of claim 120 121 or 122 wherein said clutch is provided with at least a minimum level of engagement during said predetermined times intervals and wherein engagement of said clutch does not increase if a difference between speeds of said drivelines is less than said predetermined value during said predetermined time intervals the magnitude of said steps decreases as said minimum level of engagement of said clutch increases.

127. (Currently Amended): The adaptive drive system of claim 125 wherein said predetermined value at said predetermined time intervals may vary based on operating conditions including at least one of throttle position, vehicle speed, steering angle; brake condition; and identity of an overrunning driveline microcontroller determines said minimum level of clutch engagement in response to a signal from a throttle position sensor.

128. (Cancelled)

- 129. (Currently Amended): The adaptive drive system of claim 121 or 122 wherein the magnitude of said steps are a function of one of throttle position and brake system activation.
- 130. (Previously Presented): The adaptive drive system of claim 120 wherein said clutch is a friction clutch pack having a plurality of interleaved discs.

Attorney Docket No. DKT91043H

- 131. (Currently Amended): The adaptive drive system of claim [[120]] 130 further including a ball ramp actuator having an electromagnetic coil.
- 132. (Currently Amended): An adaptive drive system for a motor vehicle comprising, in combination,

a first drive line having a first drive shaft, a first differential, a first pair of axles, a first pair of wheels and at lease one first speed sensor for providing a first drive line speed signal,

a second drive line having a second drive shaft, a second differential, a second pair of axles, a second pair of wheels and at least one second speed sensor for providing a second drive line speed signal,

a transfer case having an input, a first output adapted to drive said first drive line, a second output adapted to drive said second drive line and a clutch that is capable of being variably engaged and is operably disposed between said first output and said second output, and

a microcontroller that receives said first driveline speed signal from said first speed sensor and said second driveline speed signal from said second speed sensor and then determines a speed difference between said first and said second speed signals at predetermined times,

and wherein said clutch engagement increases if said speed difference is greater than a [[first]] predetermined value at said predetermined times and said clutch engagement decreases if said speed difference is less than <u>another a second</u> predetermined value at <u>another of said predetermined times</u>.



Attorney Docket No. DKT91043H

- 133. (Previously Presented): An adaptive drive system for a motor vehicle of claim 132 wherein said clutch is a friction clutch pack having a plurality of interleaved discs.
- 134. (Currently Amended): An adaptive drive system for a motor vehicle of claim 133 [[132]] further including a ball ramp actuator <u>having an electromagnetic coil</u>.
- . 135. (Currently Amended): An adaptive drive system for a motor vehicle of claim 132 wherein said clutch is engaged [[at]] to at least a minimum level of engagement during said predetermined times intervals.
- 136. (Previously Presented): An adaptive drive system for a motor vehicle of claim 135 wherein said microcontroller determines said minimum level of clutch engagement in response to a signal from a throttle position sensor.
- 137. (Currently Amended): An adaptive drive system for a motor vehicle of claim 132 wherein said increased engagement of said clutch occurs in steps when said speed difference exceeds said [[first]] predetermined value during said predetermined times time intervals.
- 138. (Currently Amended): An adaptive drive system for a motor vehicle of claim 132 wherein said decreased engagement of said clutch occurs in steps when said

Attorney Docket No. DKT91043H

speed difference does not exceed said second predetermined value during said predetermined time intervals.

BHGL

- 139. (New) An adaptive drive system for a motor vehicle of claim 137 wherein said steps are equal in magnitude.
- 140. (New) An adaptive drive system for a motor vehicle of claim 138 wherein said steps are equal in magnitude
- 141. (New) An adaptive drive system of claim 108 further including a ball ramp actuator and an electromagnetic coil.
- 142. (New) An adaptive drive system of claim 108 wherein said predetermined value and said another predetermined value are the same.
- 143. (New) An adaptive drive system of claim 108 wherein said predetermined value and said another predetermined value are different.
- 144. (New) The adaptive drive system of claim 112 wherein said amounts of increased and decreased engagement may vary are equal.

Attorney Docket No. DKT91043H

- 145. (New) The adaptive drive system of claim 120 wherein engagement of said clutch decreases if a difference between speeds of said drivelines is less than said predetermined value during said predetermined time intervals.
- 146 (New) The adaptive drive system of claim 132 wherein said predetermined value and said another predetermined value are the same.
- 147. (New) The adaptive drive system of claim 132 wherein said predetermined value and said another predetermined value are different.

